# PETRO-CANADA ATF D3M



### 000003001076

Version 5.0 Revision Date 2017/01/06 Print Date 2017/01/06

#### **SECTION 1. IDENTIFICATION**

Product name : PETRO-CANADA ATF D3M

Synonyms : RDL 2746

Product code : ATFD3MP5R, ATFD3MP20, ATFD3MICT, ATFD3MIBC,

ATFD3MDRR, ATFD3MDRM, ATFD3MDCT, ATFD3MC12,

ATFD3M, ATFD3MBLK

Manufacturer or supplier's details

Petro-Canada Lubricants Inc. 2310 Lakeshore Road West Mississauga ON L5J 1K2

Canada

Emergency telephone num-

ber

Petro-Canada Lubricants Inc.: +1 905-403-5770;

Canutec Transportation: 1-888- 226-8832 (toll-free) or 613-

996-6666;

Poison Control Centre: Consult local telephone directory for

emergency number(s).

## Recommended use of the chemical and restrictions on use

Recommended use : Automatic transmission fluid for most North American auto-

mobiles and for off-highway torque converters requiring C-4 type transmission fluid. It is also suitable as a hydraulic fluid and as a top-up in power steering systems. Not to be used in

conditions where aerosols could be generated.

Prepared by : Product Safety: +1 905-804-4752

## **SECTION 2. HAZARDS IDENTIFICATION**

### **Emergency Overview**

Appearance	viscous liquid
Colour	dark red
Odour	Mild petroleum oil like.

#### **GHS Classification**

Not a hazardous substance or mixture.

#### **GHS** label elements

Not a hazardous substance or mixture.

## **Potential Health Effects**

Primary Routes of Entry : Eye contact

TM\* Trademark of Petro-Canada Lubricants Inc.

TM Trademark of Suncor Energy Inc. Used under licence.

# PETRO-CANADA ATF D3M



#### 000003001076

Version 5.0 Revision Date 2017/01/06 Print Date 2017/01/06

Ingestion Inhalation Skin contact

Aggravated Medical Condi-

tion

: None known.

Other hazards

None known.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**ACGIH** No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by ACGIH.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### **Hazardous components**

Chemical name	CAS-No.	Concentration
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	30 - 50 %
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	40 - 60 %
Methacrylate copolymers		1 - 3 %

#### **SECTION 4. FIRST AID MEASURES**

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

<sup>™</sup> Trademark of Petro-Canada Lubricants Inc.

<sup>™</sup> Trademark of Suncor Energy Inc. Used under licence.

# PETRO-CANADA ATF D3M



#### 000003001076

Version 5.0 Revision Date 2017/01/06 Print Date 2017/01/06

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a physi-

cian or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms and effects, both acute and

delayed

: First aider needs to protect himself.

### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

: No information available.

Specific hazards during fire-

fighting

: Cool closed containers exposed to fire with water spray.

Hazardous combustion prod-

ucts

 Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), hydrocarbons, smoke and irritating vapours as products of incomplete com-

bustion.

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

: Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.

Environmental precautions : Do not allow uncontrolled discharge of product into the envi-

ronment.

Methods and materials for containment and cleaning up

: Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.

Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation.

Contact the proper local authorities.

### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

TM\* Trademark of Petro-Canada Lubricants Inc.

<sup>™</sup> Trademark of Suncor Energy Inc. Used under licence.

# PETRO-CANADA ATF D3M



#### 000003001076

Version 5.0 Revision Date 2017/01/06 Print Date 2017/01/06

plication area.

Use only with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition.

Keep container closed when not in use.

Conditions for safe storage : Store in original container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct sun-

light.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhalable fraction)	5 mg/m3	ACGIH

**Engineering measures** 

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

## Personal protective equipment

Respiratory protection

: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

Internet: lubricants.petro-canada.com/sds

Page: 4 / 9

TM\* Trademark of Petro-Canada Lubricants Inc.

<sup>™</sup> Trademark of Suncor Energy Inc. Used under licence.

# PETRO-CANADA ATF D3M



#### 000003001076

Version 5.0 Revision Date 2017/01/06 Print Date 2017/01/06

working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Protective measures : Wash contaminated clothing before re-use.

Hygiene measures : Remove and wash contaminated clothing and gloves, includ-

ing the inside, before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : viscous liquid

Colour : dark red

Odour : Mild petroleum oil like.

Odour Threshold : No data available

Pour point : No data available

Pour point : -51 °C (-60 °F)

Boiling point/boiling range : No data available

Flash point : 185 °C (365 °F)

Method: Cleveland open cup

Fire Point : 205 °C (401 °F)

Auto-Ignition Temperature : No data available Evaporation rate : No data available

Flammability : Low fire hazard. This material must be heated before ignition

will occur.

Upper explosion limit : No data available

Lower explosion limit : No data available

Internet: lubricants.petro-canada.com/sds

Page: 5 / 9

TM\* Trademark of Petro-Canada Lubricants Inc.

<sup>™</sup> Trademark of Suncor Energy Inc. Used under licence.

# PETRO-CANADA ATF D3M



#### 000003001076

Version 5.0 Revision Date 2017/01/06 Print Date 2017/01/06

Vapour pressure : No data available

Relative vapour density

No data available

Density : 0.855 kg/l (15 °C / 59 °F)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, kinematic : 34.26 cSt (40 °C / 104 °F)

7.7 cSt (100 °C / 212 °F)

Explosive properties : Do not pressurise, cut, weld, braze, solder, drill, grind or ex-

pose containers to heat or sources of ignition.

## **SECTION 10. STABILITY AND REACTIVITY**

Possibility of hazardous reac-

tions

: Hazardous polymerisation does not occur.

Stable under normal conditions.

Conditions to avoid : No data available

Incompatible materials : Reactive with oxidising agents, reducing agents and acids.

Hazardous decomposition

products

: May release COx, smoke and irritating vapours when heated

to decomposition.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact

# **Acute toxicity**

## **Product:**

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal

toxicity

TM\* Trademark of Petro-Canada Lubricants Inc.

<sup>™</sup> Trademark of Suncor Energy Inc. Used under licence.

# PETRO-CANADA ATF D3M



#### 000003001076

Version 5.0 Revision Date 2017/01/06 Print Date 2017/01/06

#### **Components:**

## lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

# lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

### Skin corrosion/irritation

#### **Product:**

Remarks: No data available

## Serious eye damage/eye irritation

### **Product:**

Remarks: No data available

### Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

## Reproductive toxicity

No data available

### STOT - single exposure

No data available

## STOT - repeated exposure

No data available

Internet: lubricants.petro-canada.com/sds TM\* Trademark of Petro-Canada Lubricants Inc.

<sup>™</sup> Trademark of Suncor Energy Inc. Used under licence.

# PETRO-CANADA ATF D3M



#### 000003001076

Version 5.0 Revision Date 2017/01/06 Print Date 2017/01/06

### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

**Product:** 

Toxicity to fish

Remarks: No data available

Toxicity to daphnia and other

aquatic invertebrates

Remarks: No data available

Toxicity to algae

Remarks: No data available

Toxicity to bacteria : Remarks: No data available

## Persistence and degradability

**Product:** 

Biodegradability : Remarks: No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

#### Other adverse effects

No data available

## **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

# International Regulations

#### IATA-DGR

Not regulated as a dangerous good

**IMDG-Code** 

Internet: lubricants.petro-canada.com/sds

Page: 8 / 9

TM\* Trademark of Petro-Canada Lubricants Inc.

<sup>™</sup> Trademark of Suncor Energy Inc. Used under licence.

# PETRO-CANADA ATF D3M



#### 000003001076

Version 5.0 Revision Date 2017/01/06 Print Date 2017/01/06

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **National Regulations**

**TDG** 

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

## The components of this product are reported in the following inventories:

**DSL** On the inventory, or in compliance with the inventory

**TSCA** All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

IECSC On the inventory, or in compliance with the inventory
EINECS On the inventory, or in compliance with the inventory

#### **SECTION 16. OTHER INFORMATION**

For Copy of SDS : Internet: lubricants.petro-canada.com/sds

Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-

4518

Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-

800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax:

1-800-201-6285

For Product Safety Information: 1 905-804-4752

Prepared by : Product Safety: +1 905-804-4752

Revision Date : 2017/01/06

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.