



L'huile des records du monde

GALAXIE - SAE 15W-50

100% synthetic oil - for competition engines

APPLICATIONS

Specially formulated to meet the requirements of **modern competition engines**.

Particularly recommended for highly stressed gasoline engines (turbocharged, multi-valved), used under racing or sporty driving conditions.

Suitable for catalytic converters and for turbo Diesel engines.

MAIN PHYSICAL DATA

		Units	15W-50
Density at	20° C	kg/m ³	854
Kinematic viscosity at	40° C	mm ² /s	125
Kinematic viscosity at	100° C	mm ² /s	18,3
Viscosity index			164
Pour point		° C	- 46
Flash point Cleveland open cup		°C	224
Dynamic viscosity at	- 20°C	mPa.s	4000

The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- **Excellent stability of the oil film** at high temperature
- High **detergent** and **dispersant** properties
- Maintains the **original performances** of the engine.
- **Stable oil pressure** at high temperature
- **Optimal protection** against deposit formation
- Formulation based on synthetic **esters** providing an increased resistance to volatility.

PERFORMANCES

GALAXIE exceeds the requirements of the major OEM, and the recommendations of the API SL/CF and ACEA A3/B4 classifications.

