



L'huile des records du monde

GALAXIE GT - SAE 5W-50

100% synthetic oil for competition

APPLICATIONS

This 100% synthetic lubricant is formulated with polyalphaolefins (PAO) and esters ensuring an optimal lubrication under extreme service conditions.

For highly stressed sport or grand touring engines used on roads or circuits.

Initially developed for gasoline engines, turbocharged-or-not, multivalve-or-not, this lubricant is also suitable for LPG and Diesel engines.

Also adapted to any engine for which the manufacturer recommends or specifies the use of an SAE 5W-50 meeting one of the specifications indicated below.

MAIN PHYSICAL DATA

		Units	5W-50
Density at	20° C	kg/m ³	851
Kinematic viscosity at	40° C	mm ² /s	110
Kinematic viscosity at	100° C	mm ² /s	17.7
Viscosity index			172
Pour point		° C	- 45
Flash point Cleveland open cup		°C	234
Dynamic viscosity at	- 30°C	mPa.s	5500

The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- **Excellent shear resistance maintaining a thick oil film** at hot temperature even under severe service conditions
- **SAE 5W viscosity and 100 % formula** provide easy start-ups and quick engine protection at cold temperature.
- **Reinforced thermal stability** preventing deposits formation
- Very **low volatility** allowing to reduce oil consumption
- Excellent detergent-dispersant properties keeping the engine clean

SPECIFICATIONS

API SN/CF (exceeds the API SG, SH, SJ, SL and SM requirements)

ACEA A3/B3-10 & ACEA A3/B4-07

MB 229.3 ; VW 502.00/ 505.00