

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS #: 39334 **RUBIA TIR 9900 FE 5W-30**

Date of the previous version: 2016-03-15 **Revision Date: 2016-03-22** Version 3.03

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE

COMPANY/UNDERTAKING

1.1. Product identifier

RUBIA TIR 9900 FE 5W-30 Product name

Number 1YW Substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Motor oil. Identified uses

1.3. Details of the supplier of the safety data sheet

Supplier A - TOTAL UK LIMITED

One Euston Square

40 Melton Street. London. NW1 2FD

UNITED KINGDOM Tel: +44 (0)20 7339 8000 Fax: +44 (0)20 7339 8033

B-TOTAL LUBRIFIANTS 562 Avenue du Parc de L'ile

92029 Nanterre Cedex

FRANCE

Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71

For further information, please contact:

Contact Point A - Specific Product Related Info: 01977 636200

B - HSE

E-mail Address A - rm.gb-msds@total.co.uk

B - rm.msds-lubs@total.com

1.4. Emergency telephone number

00 33 149 00 00 49 (24h/24, 7d/7) TOTAL UK ltd: + 44 (0) 20 7339 8000

For Lubricants only: TOTAL Lubricants - +44 (0)1977 636200 For bitumen only: Total Bitumen -+44 (0) 17 7272 9302

UK: National Poisons Information Service (NPIS): NHS111 or a doctor



RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 **Version** 3.03

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008

For the full text of the H-Statements mentioned in this Section, see Section 2.2.

Classification

The product is classified as dangerous in accordance with Regulation (EC) No. 1272/2008 Serious eye damage/eye irritation - Category 2 - (H319)

2.2. Label elements

Labelled according to

REGULATION (EC) No 1272/2008



Signal Word WARNING

Hazard Statements

H319 - Causes serious eye irritation

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P280 - Wear eye protection/ face protection

Contains C14-16-18 Alkyl phenol May produce an allergic reaction

2.3. Other hazards

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture

Hazardous components



RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 **Version** 3.03

Chemical Name	EC-No	REACH Registration Number	CAS-No	Weight %	GHS Classification
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	276-738-4	01-2119474889-13	72623-87-1	50-<60	Asp. Tox. 1 (H304)
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	500-183-1	01-2119486452-34	68037-01-4	10-<20	Asp. Tox. 1 (H304)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	265-169-7	01-2119471299-27	64742-65-0	3-<5	Asp. Tox. 1 (H304)
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydro xyphenyl)propionate	406-040-9	01-0000015551-76	125643-61-0	1-<2.5	Aquatic Chronic 4 (H413)
bis(nonylphenyl)amine	253-249-4	01-2119488911-28	36878-20-3	1-<2.5	Aquatic Chronic 4 (H413)
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	298-577-9	01-2119543726-33	93819-94-4	1-<2.5	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Aquatic Chronic 2 (H411)
C14-16-18 Alkyl phenol	-	01-2119498288-19	۸	0.1-<0.25	Skin Sens. 1 (H317) Aquatic Chronic 4 (H413)

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR

EMERGENCY MEDICAL CARE.

Eye contact Rinse thoroughly with plenty of water, also under the eyelids.

Skin contact Remove contaminated clothing and shoes. Wash off with soap and water. Wash

contaminated clothing before reuse.

Inhalation Move to fresh air.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control centre immediately.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact Causes serious eye irritation.

Skin contact Not classified. May produce an allergic reaction.

Inhalation Not classified. Inhalation of vapours in high concentration may cause irritation of respiratory

system.



RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 Version 3.03

Ingestion Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhoea.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing MediaDo not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may

be highly dangerous if inhaled in confined spaces or at high concentration.

5.3. Precautions for fire-fighters

Special protective equipment for

fire-fighters

Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing

water must be disposed of in accordance with local regulations.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition.

6.2. Environmental precautions

General InformationDo not allow material to contaminate ground water system. Try to prevent the material from

entering drains or water courses. Local authorities should be advised if significant spillages

cannot be contained.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up

Dam up. Contain spillage, and then collect with non-combustable absorbent material, (e.g.

sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for

disposal.



RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 Version 3.03

6.4. Reference to other sections

Personal protective equipment See Section 8 for more detail.

Waste treatment See section 13.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8. Use only in

well-ventilated areas. Do not breathe vapours or spray mist. Avoid contact with skin, eyes

and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges: Ground/bond containers, tanks

and transfer/receiving equipment.

Hygiene measuresEnsure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do

not use abrasives, solvents or fuels. Do not dry hands with rags that have been

contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Preferably keep in the original container. Otherwise, reproduce all the statutory information from the labels onto the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.

Materials to avoid Strong oxidising agents.

7.3. Specific use(s)

Specific use(s) No information available.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parametres

Exposure limits Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH

(TLV) TWA 5 mg/m³ (highly refined)

Legend See section 16

DNEL Worker (Industrial/Professional)



RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 Version 3.03

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1				5.4 mg/m³/8h (aerosol - inhalation)
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0				5.4 mg/m³/8h (aerosol - inhalation)
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hy droxyphenyl)propionate 125643-61-0	20 mg/kg Dermal	1 mg/cm2 Dermal	0.22 mg/kg Dermal	0.006 mg/cm2 Dermal
bis(nonylphenyl)amine 36878-20-3			0.62 mg/kg bw/day Dermal 4.37 mg/m³ Inhalation	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) 93819-94-4			0.58 mg/kg Dermal 8.31 mg/m³ Inhalation	

DNEL Consumer

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1				1.2 mg/m³/24h (aerosol - inhalation)
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0				1.2 mg/m³/24h (aerosol - inhalation)
bis(nonylphenyl)amine 36878-20-3			0.31 mg/kg bw/day Dermal 1.09 mg/m³ Inhalation 0.31 mg/kg bw/day Oral	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) 93819-94-4			0.29 mg/kg Dermal 2.11 mg/m³ Inhalation 0.24 mg/kg Oral	

Predicted No Effect Concentration (PNEC)

Chemical Name	Water	Sediment	Soil	Air	STD	Oral
Cilcillical Name	vvale:	Jeuillelli	5011	AII AII	JIF	Orai



SDS #: 39334 RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 Version 3.03

Lubricating oils (petroleum),					9.33 mg/kg food
C20-50,					
hydrotreated neutral					
oil-based					
72623-87-1					
reaction mass of	0.0043 mg/l fw	233 mg/kg fw dw	189 mg/kg		
isomers of:	0.00043 mg/l mw	23.3 mg/kg mw			
C7-9-alkyl		dw			
3-(3,5-di-trans-butyl-					
4-hydroxyphenyl)pro					
pionate					
125643-61-0					
bis(nonylphenyl)ami	0.1 mg/l fw	132000 mg/kg dw	263000 mg/kg dw	1 mg/l	
ne	0.01 mg/l mw	fw			
36878-20-3	1 mg/l or	13200 mg/kg dw			
		mw			
zinc	0.004 mg/l fw	0.0116 mg/kg dw	0.00528 mg/kg	100 mg/l	10.67 mg/kg food
bis[O-(6-methylhept	0.0046 mg/l mw	fw	soil dw	_	
yl)]	0.021 mg/l or	0.00116 mg/kg			
bis[O-(sec-butyl)]		dw mw			
bis(dithiophosphate)					
93819-94-4					

8.2. Exposure controls

Occupational Exposure Controls

Engineering measures

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Personal protective equipment

General Information

If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.

Respiratory protection

None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387): Type A/P2. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

Eye protection

If splashes are likely to occur, wear:. Safety glasses with side-shields.

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.

Hand protection

Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency.



RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 Version 3.03

Environmental exposure controls

General Information The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Clear Colour brown

Physical state @20°C Liquid

Odour No information available **Odour Threshold** No information available

Method **Property** <u>Values</u> Remarks

No information available pН Melting point/range No information available

Boiling point/boiling range No information available

Cleveland Open Cup (COC) Flash point 224 °C 435 °F Cleveland Open Cup (COC)

No information available **Evapouration rate** Flammability Limits in Air No information available Vapour pressure No information available Vapour density No information available

Relative density No information available

Density 848 - 868 kg/m³ @ 15 °C ISO 12185

Water solubility Not applicable

Solubility in other solvents No information available logPow No information available **Autoignition temperature** No information available

Decomposition temperature No information available

Viscosity, kinematic 70.4 mm2/s @ 40 °C ISO 3104 12.10 - 12.40 mm2/s @ 100 °C ISO 3104

Explosive properties Not explosive Not applicable Oxidising properties Possibility of hazardous reactions Not applicable

9.2. Other information

Freezing point No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

No information available. **General Information**



RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 Version 3.03

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions None under normal processing.

10.4. Conditions to Avoid

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products None under normal use.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact . Not classified. May produce an allergic reaction.

Eye contact . Causes serious eye irritation.

Inhalation . Not classified. Inhalation of vapours in high concentration may cause irritation of

respiratory system.

Ingestion . Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhoea.

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	LD50 > 5000 mg/kg bw (rat - OECD 401)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	LD50 > 5000 mg/kg (Rat)	LD50 > 2000 mg/kg (Rat)	LC50 (4h) > 5.2 mg/l (Rat)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5.53 mg/l (aerosol) (rat - OECD 403)
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propi onate		LD50 > 2000 mg/kg (Rat - OECD 402)	



RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 Version 3.03

bis(nonylphenyl)amine	LD50 > 5000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rat - OECD 402)	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	LD50 2600 mg/kg (Rat)	LD50 > 3160 mg/kg (Rabbit - OECD 402)	

Sensitisation

Sensitisation Not classified as a sensitizer. Contains senitizer(s). May produce an allergic reaction.

Specific effects

Carcinogenicity This product is not classified carcinogenic. During use in engines, contamination of oil with

low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil

is thoroughly removed by washing with soap and water.

Mutagenicity This product is not classified as mutagenic.

Reproductive toxicityThis product does not present any known or suspected reproductive hazards.

Repeated Dose Toxicity

Subchronic Toxicity No information available.

Target Organ Effects (STOT)

Target Organ Effects (STOT) No information available.

Other information

Other adverse effects Characteristic skin lesions (oil blisters) may develop following prolonged and repeated

exposures (contact with contaminated clothing).

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Not classified.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and	Toxicity to fish	Toxicity to
		other aquatic	-	microorganisms
		invertebrates.		



RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 Version 3.03

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1	EL50 (48h) > 100 mg (Pseudokirchnerella subcapitata - OECD 201)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202) LL50 (24h) > 10000 mg/l (Gammarus pulex - OECD 202) LL50 (48h) > 10000 mg/l (Gammarus pulex - OECD 202) LL50 (72h) > 10000 mg/l	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
		(Gammarus pulex - OECD 202) LL50 (96h) > 10000 mg/l (Gammarus pulex - OECD 202)		
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated 68037-01-4	EL50 (72h) > 1000 mg/l (Scenedesmus capricornutum - OECD 201)	EC50 (48h) 190 mg/l (Daphnia magna) LE50(48h) > 1000 mg/l (Daphnia magna)	LC50(96h) > 750 mg/l (Pimephales promelas) LL50(96h) > 1000 mg/l (Pimephales promelas)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0		EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydro xyphenyl)propionate 125643-61-0	EC50 (72h) > 3 mg/l (Scenedesmus sp OECD 201)	EC50(24h) > 100 mg/l (Daphnia magan - OECD 202)	LC50 (96h) > 74 mg/l (Brachydanio rerio - semi static - OECD 203)	
bis(nonylphenyl)amine 36878-20-3	EC50 (72h) > 100 mg/l (Desmodesmus subspicatus - OECD 201)	EC50 (48h) > 100 mg/l (Daphnia magna - OECD 202)	LC50 (96h) > 100 mg/l (Brachyanio rerio - OECD 203)	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) 93819-94-4	EbC50 (96h) 2.1 mg/l Selenastrum capricornutum (OECD 201)	EL50 (48h) 5.4 mg/l Daphnia magna (OECD 202)	LC50 (96h) 4.5 mg/l Oncorhynchus mykiss (OECD 203)	
C14-16-18 Alkyl phenol		EC50(48h) > 100 mg/l (Daphnia magna - static - OECD202)		

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

No information available.

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1		NOEL (21d) 10 mg/l (Daphnia magna - OECD 211)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox) NOEL (96h) > 100 mg/l (Pimephales promelas - OECD 203)	
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated 68037-01-4	NOELR (72h) 1000 mg/l (Scenedesmus capricornutum - OECD 201)	NOELR (21d) 125 mg/l (Daphnia magna - OECD 211)		



RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 Version 3.03

Distillates (petroleum),	NOEL (21d) 10 mg/l	NOEL (14/28d) > 1000 mg/l	
solvent-dewaxed heavy	(Daphnia magna - OECD	(Oncorhynchus mykiss -	
paraffinic	211)	QSAR Petrotox)	
64742-65-0			

Effects on terrestrial organisms

No information available.

12.2. Persistence and Degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information

Chemical Name	log Pow
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based - 72623-87-1	4.1
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate - 125643-61-0	9.2
bis(nonylphenyl)amine - 36878-20-3	7.7
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) - 93819-94-4	0.9

12.4. Mobility in soil

Soil Given its physical and chemical characteristics, the product generally shows low soil

mobility.

Air Loss by evaporation is limited.

Water Insoluble. The product spreads on the surface of the water.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

12.6. Other adverse effects

General Information No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods



RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 **Version** 3.03

Waste from residues / unused

products

Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is

forbidden.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EWC Waste Disposal NoThe following Waste Codes are only suggestions:. 13 02 05. According to the European

Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was

used.

Section 14: TRANSPORT INFORMATION

ADR/RID not regulated

IMDG/IMO not regulated

ICAO/IATA not regulated

ADN not regulated

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Further information

No information available

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available

15.3. National regulatory information

The United Kingdom

Avoid exceeding occupational exposure limits (see section 8).



RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 Version 3.03

Ireland

· Avoid exceeding occupational exposure limits (see section 8).

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H411 - Toxic to aquatic life with long lasting effects

H413 - May cause long lasting harmful effects to aquatic life

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

DNEL = Derived No Effect Level

PNEC = Predicted No Effect Concentration

dw = dry weight

fw = fresh water

mw = marine water

or = occasional release

Legend Section 8

TWA: Time Weight Average STEL: Short Time Exposure Limit

+ Sensitiser * Skin designation

** Hazard Designation C: Carcinogen

** Toxic to reproduct

M: Mutagen R: Toxic to reproduction

Revision Date: 2016-03-22

Revision Note *** Indicates updated section.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006



RUBIA TIR 9900 FE 5W-30

Revision Date: 2016-03-22 Version 3.03

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of Safety Data Sheet