000003000258

# DURADRIVE <sup>™</sup> MV SYNTHETIC ATF



### Version 5.0 Revision Date 2016/08/23 Print Date 2016/08/23 **SECTION 1. IDENTIFICATION** : DURADRIVE <sup>™</sup> MV SYNTHETIC ATF Product name Synonyms : RDL 3542 Product code DDMVATFICT, DDMVATFP20, DDMVATFIBC, • DDMVATFDRR, DDMVATFDRM, DDMVATFDCT, DDMVATFC12, DDMVATF, DDMVATFBLK Manufacturer or supplier's details Petro-Canada Lubricants Inc. 2310 Lakeshore Road West Mississauga ON L5J 1K2 Canada Emergency telephone num-Suncor Energy: +1 403-296-3000; Canutec Transportation: 1-888- 226-8832 (toll-free) or 613ber 996-6666; Poison Control Centre: Consult local telephone directory for emergency number(s). Recommended use of the chemical and restrictions on use A synthetic multi-vehicle ATF formulated to meet the perfor-Recommended use : mance needs of most North American, Asian and European automatic transmissions.

# Prepared by

## SECTION 2. HAZARDS IDENTIFICATION

:

#### Emergency Overview

viscous liquid	
red	
Mild petroleum oil like.	
	red

Product Safety: +1 905-804-4752

### **GHS Classification**

Not a hazardous substance or mixture.

#### **GHS** label elements

Not a hazardous substance or mixture.

#### **Potential Health Effects**

Primary Routes of Entry

: Eye contact Ingestion Inhalation Skin contact

# DURADRIVE <sup>™</sup> MV SYNTHETIC ATF



## 000003000258

Version 5.0	Revision Date 2016/08/23	Print Date 2016/08/23
Aggravated Medical Condi- tion	: None known.	
Other hazards None known.		
IARC	No component of this product present at equal to 0.1% is identified as probable, po human carcinogen by IARC.	5
ACGIH	No component of this product present at equal to 0.1% is identified as a carcinoge gen by ACGIH.	5

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

### Hazardous components

Chemical name	CAS-No.	Concentration
lubricating oils (petroleum), C15-30, hydrotreat- ed neutral oil-based	72623-86-0	50 - 70 %
lubricating oils (petroleum), C20-50, hydrotreat- ed neutral oil-based	72623-87-1	10 - 20 %
Mineral oil		1 - 5 %
distillates (petroleum), hydrotreated light paraf- finic	64742-55-8	1 - 5 %
1-(tert-dodecylthio)propan-2-ol	67124-09-8	0.1 - 1%

### **SECTION 4. FIRST AID MEASURES**

Petro-Canada is a Suncor Energy business.

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water.
Internet: lubricants.petro-canada.ca/msds		Page: 2 / 9

™ Trademark of Suncor Energy Inc. Used under licence.

# DURADRIVE <sup>™</sup> MV SYNTHETIC ATF

## 000003000258



Version 5.0	Revision Date 2016/08/23	Print Date 2016/08/23
	DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.	
Most important symptoms and effects, both acute and delayed	: First aider needs to protect himsel	f.

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	-
Unsuitable extinguishing media	: No information available.	
Specific hazards during fire- fighting	: Cool closed containers exposed to fire with water spray.	
Hazardous combustion prod- ucts	: Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), smoke and irritating vapours as products of incomplete combustion.	
Further information	: Prevent fire extinguishing water from contaminating surface water or the ground water system.	

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

## SECTION 7. HANDLING AND STORAGE

Advice on safe handling	<ul> <li>For personal protection see section 8.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>In case of insufficient ventilation, wear suitable respiratory equipment.</li> </ul>
-------------------------	---

# DURADRIVE <sup>™</sup> MV SYNTHETIC ATF

## 000003000258



Version 5.0	Revision Date 2016/08/23	Print Date 2016/08/23
	<ul> <li>Avoid contact with skin, eyes and clothing. Do not ingest.</li> <li>Keep away from heat and sources of ignition.</li> <li>Keep container closed when not in use.</li> <li>Store in original container.</li> <li>Containers which are opened must be carefully resealed and kept upright to prevent leakage.</li> <li>Keep in a dry, cool and well-ventilated place.</li> <li>Keep in properly labelled containers.</li> <li>To maintain product quality, do not store in heat or direct sunlight.</li> </ul>	
Conditions for safe storage		

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH

**Engineering measures** : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

### Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Filter type	:	organic vapour filter

## Hand protection

# DURADRIVE <sup>™</sup> MV SYNTHETIC ATF



## 000003000258

Version 5.0	Revision Date 2016/08/23	Print Date 2016/08/23
Material	: neoprene, nitrile, polyvinyl alcohol	(PVA), Viton(R).
Remarks	: Chemical-resistant, impervious glo approved standard should be wor chemical products if a risk assess essary.	n at all times when handling
Eye protection	: Wear face-shield and protective s problems.	uit for abnormal processing
Skin and body protection	: Choose body protection in relation tration and amount of dangerous s cific work-place.	
Protective measures	<ul> <li>Wash hands and face before breat handling the product.</li> <li>Wash contaminated clothing before Ensure that eyewash station and station to the work-station location.</li> </ul>	re re-use.
Hygiene measures	: Remove and wash contaminated ing the inside, before re-use. Wash face, hands and any expose handling.	

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: viscous liquid
Colour	: red
Odour	: Mild petroleum oil like.
Odour Threshold	: No data available
рН	: No data available
Pour point	: -54 °C (-65 °F)
Boiling point/boiling range	: No data available
Flash point	: 182 °C (360 °F) Method: Pensky-Martens closed cup
Fire Point	: 223 °C (433 °F)
Auto-Ignition Temperature	: No data available
Evaporation rate	: No data available
Flammability	: Low fire hazard. This material must be heated before ignition will occur.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available

Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.

# DURADRIVE <sup>™</sup> MV SYNTHETIC ATF



## 000003000258

Version 5.0	Revision Date 2016/08/23	Print Date 2016/08/23
Relative vapour density	: No data available	
Relative density	: No data available	
Density	: 0.8518 kg/l (15 °C / 59 °F)	
Solubility(ies)		
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Viscosity		
Viscosity, kinematic	: 36.1 cSt (40 °C / 104 °F)	
	7.42 cSt (100 °C / 212 °F)	
Explosive properties	: Do not pressurise, cut, weld, braze pose containers to heat or sources	

## SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	: Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	: No data available
Incompatible materials	: Reactive with oxidising agents, reducing agents and acids.
Hazardous decomposition products	: May release COx, NOx, aldehydes, smoke and irritating va pours when heated to decomposition.

## SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes Eye contact Ingestion Inhalation Skin contact	of	exposure
Acute toxicity		
Product: Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available

# DURADRIVE <sup>™</sup> MV SYNTHETIC ATF



Version 5.0	Revision Date 2016/08/23	Print Date 2016/08/23
<u>Components:</u> Iubricating oils (petroleum Acute oral toxicity	), C15-30, hydrotreated neutral oil-based: : LD50 (Rat): > 5,000 mg/kg,	
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,	
lubricating oils (petroleum Acute oral toxicity	), C20-50, hydrotreated neutral oil-based: : LD50 (Rat): > 5,000 mg/kg,	:
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,	
Skin corrosion/irritation Product:		
Remarks: No data available		
Serious eye damage/eye ir	ritation	
<u>Product:</u> Remarks: No data available		
Respiratory or skin sensiti	sation	
No data available		
<b>Germ cell mutagenicity</b> No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
<b>STOT - single exposure</b> No data available		
STOT - repeated exposure		
No data available		



# DURADRIVE <sup>™</sup> MV SYNTHETIC ATF

## 000003000258

Version 5.0

Print Date 2016/08/23

## **SECTION 12. ECOLOGICAL INFORMATION**

Ecotoxicity	
<u>Product:</u> Toxicity to fish	: Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	: Remarks: No data available
Toxicity to algae	: Remarks: No data available
Toxicity to bacteria	: Remarks: No data available
Persistence and degradabilit	у
Product:	
Biodegradability	: Remarks: No data available
<b>Bioaccumulative potential</b> No data available	
Mobility in soil	
No data available	
Other adverse effects	
No data available	

## SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	<ul> <li>The product should not be allowed to enter drains, water courses or the soil.</li> <li>Offer surplus and non-recyclable solutions to a licensed disposal company.</li> <li>Waste must be classified and labelled prior to recycling or disposal.</li> <li>Send to a licensed waste management company.</li> <li>Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.</li> </ul>

## **SECTION 14. TRANSPORT INFORMATION**

## International Regulations

## IATA-DGR


Not regulated as a dangerous good

### IMDG-Code

Not regulated as a dangerous good Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.



# DURADRIVE <sup>™</sup> MV SYNTHETIC ATF



Version 5.0

Revision Date 2016/08/23

Print Date 2016/08/23

## **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable for product as supplied.

#### National Regulations

#### TDG

Not regulated as a dangerous good

## **SECTION 15. REGULATORY INFORMATION**

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The components of this product are reported in the following inventories:		
DSL	On the inventory, or in compliance with the inventory	
TSCA	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.	
ELINCS	At least one component is not listed in EINECS but all such components are listed in ELINCS.	

### **SECTION 16. OTHER INFORMATION**

For Copy of SDS	:	Internet: lubricants.petro-canada.ca/msds Western Canada, telephone: 1-800-661-1199; fax: 1-800-378- 4518 Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1- 800-201-6285 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285 For Product Safety Information: 1 905-804-4752
Prepared by	:	Product Safety: +1 905-804-4752
Revision Date	:	2016/08/23

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

