

Mobil 1 5W-50

Most Advanced Performance Synthetic Engine Oil

Product Description

Mobil 1 5W-50 is the most advanced performance synthetic engine oil designed to provide ultimate wear protection for a smooth driving experience every time. Mobil 1 5W-50, Rally Formula, exceeds the requirements of the industry and car manufacturers' standards required for high-performance turbo-charged, supercharged gasoline and diesel multi-valve fuel injected engines. Mobil 1 5W-50 is especially suited for high speed and severe service associated with stop and go driving. Racing or normal driving, Mobil 1 5W-50, Rally Formula, provides heavy-duty engine performance and protection for an outstanding driving experience.

Features and Benefits

Mobil 1 5W-50 is made with a patented proprietary blend of ultra high performance synthetic basestocks fortified with Supersyn Antiwear Technology, the most advanced additive system available today. Mobil 1 5W-50's wide viscosity grade together with patented Supersyn Antiwear technology provides a flexible combination of powerful protection agents to outperform in many driving situations. This oil, not only exceeds the toughest industry performance standards, it is approved by several major car manufacturers for service fill use. Cars using Mobil 1 5W-50 will perform flawlessly, no matter what the driving conditions, situation or age. Key features and benefits include:

| Features | Advantages and Potential Benefits |
|---|---|
| Active cleaning agents | Actively prevents deposits and sludge build-up to enable long and clean engine life |
| Outstanding thermal and oxidation stability | Reduces oil aging allowing extended drain interval protection |
| Lowest oil consumption | Less hydrocarbon pollution and oil make up due to evaporation |
| Race Proven Technology | Performance reserve in the most extreme driving situations |
| High Viscosity Index and Supersyn Antiwear Technology | Excellent overall lubrication and wear protection performance for all driving styles and conditions |

Applications

Mobil 1 5W-50 is recommended for all types of vehicles, suitable for use in high-performance turbo-charged, supercharged gasoline and diesel multi-valve fuel injected engines found in passenger cars, light vans and trucks.

- Mobil 1 5W-50 is suitable for all types of severe driving applications, especially demanding conditions including high speed highway and stop and go city driving.
- Mobil 1 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.



Specifications and Approvals

Mobil 1 5W-50 meets or exceeds the following industry specifications:

| | |
|------|-------------|
| ACEA | A3,B3,B4 |
| API | SM,SL,SJ,CF |

Mobil 1 5W-50 has the following builder approvals:

| | |
|------------------|---------------|
| Daimler Chrysler | 229.3 / 229.1 |
| Porsche | Approved |
| Volkswagen | 505.00 |

Typical Properties

Mobil 1 5W-50

| | |
|---|-------|
| SAE Grade | 5W-50 |
| Viscosity, ASTM D 445 | |
| cSt @ 40° C | 104.9 |
| cSt @ 100° C | 17.5 |
| Viscosity Index, ASTM D 2270 | 184 |
| Sulfated Ash, wt%, ASTM D 874 | 1.2 |
| HTHS Viscosity, mPa-s @ 150° CASTM D 4683 | 4.21 |
| Pour Point, °C, ASTM D 97 | -54 |
| Flash Point, °C, ASTM D 92 | 236 |
| Density @15 °C kg/l, ASTM D 4052 | 0.859 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil 1 with Supersyn are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.