DURON TM/MC XL 15W-40

#### 000003000741

	60
-	1
PETROC	INA

Version 3.0	Revision Date 2016/11/08	Print Date 2016/11/08
SECTION 1. IDENTIFICATION		
Product name :	DURON TM/MC XL 15W-40	
Product code :	DXL15P20, DXL15IBC, DXL15DRM, I DXL15C16, DXL15C12, DXL15, DXL1	
Manufacturer or supplier's details	Petro-Canada Lubricants Inc. 2310 Lakeshore Road West Mississauga ON L5J 1K2 Canada	
Emergency telephone num- ber	Suncor Energy: +1 403-296-3000; Canutec Transportation: 1-888- 226-8 996-6666; Poison Control Centre: Consult local to emergency number(s).	
Recommended use of the cher	nical and restrictions on use	
Recommended use :	DURON XL Synthetic Blend 15W-40 is heavy duty engine oil meeting global s 4-stroke diesel engines. It can also be tions including a wide range of compre engines, wet clutch transmissions and	standards for high speed e used in other applica- ession and spark ignition
Prepared by :	Product Safety: +1 905-804-4752	

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

• •	
Appearance	viscous liquid
Colour	Light amber.
Odour	Mild petroleum oil like.

#### **GHS Classification**

Not a hazardous substance or mixture.

#### **GHS** label elements

Not a hazardous substance or mixture.

#### **Potential Health Effects**

Primary Routes of Entry

: Eye contact Ingestion Inhalation Skin contact

DURON TM/MC XL 15W-40

#### 000003000741



••••••		
Version 3.0	Revision Date 2016/11/08	Print Date 2016/11/08
Aggravated Medical Condi- tion	: None known.	
Other hazards None known.		
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.	
ACGIH	No component of this product presen equal to 0.1% is identified as a carcin gen by ACGIH.	

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration
White mineral oil (petroleum)	8042-47-5	30 - 50 %
lubricating oils (petroleum), C20-50, hydrotreat- ed neutral oil-based, high viscosity	72623-85-9	30 - 50 %
lubricating oils (petroleum), C15-30, hydrotreat- ed neutral oil-based	72623-86-0	30 - 50 %
Zinc alkyldithiophosphate	113706-15-3	1 - 5%

#### **SECTION 4. FIRST AID MEASURES**

If inhaled	: Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	<ul> <li>In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.</li> <li>Wash skin thoroughly with soap and water or use recognized skin cleanser.</li> <li>Wash clothing before reuse.</li> <li>Seek medical advice.</li> </ul>
In case of eye contact	<ul> <li>Remove contact lenses.</li> <li>Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.</li> <li>Obtain medical attention.</li> </ul>
If swallowed	<ul> <li>Rinse mouth with water.</li> <li>DO NOT induce vomiting unless directed to do so by a physician or poison control center.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>
Internet: lubricants.petro-canada.ca/msds	Page: 2 /

# DURON TM/MC XL 15W-40



#### 000003000741

Version 3.0	Revision Date 2016/11/08	Print Date 2016/11/08
	Seek medical advice.	
Most important symptoms and effects, both acute and delayed	: First aider needs to protect himself.	

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Unsuitable extinguishing media	: No information available.	
Specific hazards during fire- fighting	: Cool closed containers exposed to fire with water spray.	
Hazardous combustion prod- ucts	<ul> <li>Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), sulphur compounds (H2S), zinc oxides (ZnOx), metal oxides, hydrocarbons, smoke and irritating vapours as products of incomplete com- bustion.</li> </ul>	
Further information	: Prevent fire extinguishing water from contaminating surface water or the ground water system.	

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	se personal protective equipment. nsure adequate ventilation. vacuate personnel to safe areas. laterial can create slippery conditions.	
Environmental precautions	o not allow uncontrolled discharge of pro onment.	duct into the envi-
Methods and materials for containment and cleaning up	revent further leakage or spillage if safe t emove all sources of ignition. oak up with inert absorbent material. on-sparking tools should be used. nsure adequate ventilation. ontact the proper local authorities.	o do so.

#### SECTION 7. HANDLING AND STORAGE

Smoking, eating and drin plication area. Use only with adequate v In case of insufficient ver equipment.	e ventilation. entilation, wear suitable respiratory
--	---

# DURON TM/MC XL 15W-40



### 000003000741

Version 3.0	Revision Date 2016/11/08	Print Date 2016/11/08
Conditions for safe storage	<ul> <li>Avoid contact with skin, eyes and Do not ingest.</li> <li>Keep away from heat and sources Keep container closed when not in</li> <li>Store in original container.</li> <li>Containers which are opened musk kept upright to prevent leakage.</li> <li>Keep in a dry, cool and well-ventill Keep in properly labelled containen To maintain product quality, do no light.</li> </ul>	of ignition. In use. In use carefully resealed and ated place. rs.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high viscosity	72623-85-9	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH

**Engineering measures** 

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Personal protective equipment

Respiratory protection

: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

# DURON TM/MC XL 15W-40



#### 000003000741

Version 3.0	Revision Date 2016/11/08	Print Date 2016/11/08
	Respirator selection must be bas exposure levels, the hazards of the working limits of the selected res	he product and the safe
Filter type	: organic vapour filter	
Hand protection Material	: neoprene, nitrile, polyvinyl alcoho	ol (PVA), Viton(R).
Remarks	: Chemical-resistant, impervious g approved standard should be wo chemical products if a risk assess essary.	rn at all times when handling
Eye protection	: Wear face-shield and protective s problems.	suit for abnormal processing
Skin and body protection	: Choose body protection in relatio tration and amount of dangerous cific work-place.	
Protective measures	: Wash contaminated clothing before	ore re-use.
Hygiene measures	: Remove and wash contaminated ing the inside, before re-use. Wash face, hands and any expose handling.	

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: viscous liquid
Colour	: Light amber.
Odour	: Mild petroleum oil like.
Odour Threshold	: No data available
рН	: No data available
Pour point	: -36 °C (-33 °F)
Boiling point/boiling range	: No data available
Flash point	: 226 °C (439 °F) Method: Cleveland open cup
Fire Point	: 247 °C (477 °F)
Auto-Ignition Temperature	: No data available
Evaporation rate	: No data available
Flammability	: Low fire hazard. This material must be heated before ignition will occur.
Upper explosion limit	: No data available

# DURON TM/MC XL 15W-40

### 000003000741



Version 3.0	Revision Date 2016/11/08	Print Date 2016/11/08
Lower explosion limit	: No data available	
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Relative density	: No data available	
Density	: 0.8662 kg/l (15 °C / 59 °F)	
Solubility(ies)		
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Viscosity		
Viscosity, kinematic	: 113.9 cSt (40 °C / 104 °F)	
	15.4 cSt (100 °C / 212 °F)	
Explosive properties	: Do not pressurise, cut, weld, braze pose containers to heat or sources	-

#### SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	: Hazardous polymerisation does not occur. Stable under normal conditions.	
Conditions to avoid	: No data available	
Incompatible materials	: Reactive with oxidizing agents and water.	
Hazardous decomposition products	: May release COx, H2S, smoke and irritating vapours w heated to decomposition.	hen

#### SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes Eye contact Ingestion Inhalation Skin contact	of exposure	
Acute toxicity		
Product: Acute oral toxicity	: Remarks: No data available	
Acute inhalation toxicity	: Remarks: No data available	
ternet: lubricants.petro-canada.ca/msds	THE	Page: 6 / 10

# DURON TM/MC XL 15W-40

#### 000003000741



sion 3.0	Revision Date 2016/11/08	Print Date 2016/11/0
Acute dermal toxicity	: Assessment: The substance or n toxicity	nixture has no acute dermal
Components:		
White mineral oil (petroleu Acute oral toxicity	u <b>m):</b> : LD50 (Rat): > 5,000 mg/kg,	
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,	
Iubricating oils (petroleun Acute oral toxicity	n <b>), C20-50, hydrotreated neutral oil-ba</b> : LD50 (Rat): > 5,000 mg/kg,	ased, high viscosity:
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,	
Iubricating oils (petroleun Acute oral toxicity	n <b>), C15-30, hydrotreated neutral oil-ba</b> : LD50 (Rat): > 5,000 mg/kg,	ased:
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,	
Skin corrosion/irritation		
<u>Product:</u> Remarks: No data available		
Serious eye damage/eye i	rritation	
Product:		
Remarks: No data available	,	
Respiratory or skin sensit	isation	
No data available		
No data available Germ cell mutagenicity No data available		
Germ cell mutagenicity		

# DURON TM/MC XL 15W-40

#### 000003000741

Version 3.0

Remarks: No data available



Print Date 2016/11/08

#### **Reproductive toxicity**

No data available

# STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

#### Product:

Toxicity to fish

Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae	:	Remarks: No data available
Toxicity to bacteria	:	Remarks: No data available
Persistence and degradabilit	y	
Product:		
Biodegradability	:	Remarks: No data available
Bioaccumulative potential		
No data available		
Mobility in soil		
No data available		
Other adverse effects		
No data available		

2

#### SECTION 13. DISPOSAL CONSIDERATIONS

<ul> <li>The product should not be allowed to enter drains, water courses or the soil.</li> <li>Offer surplus and non-recyclable solutions to a licensed disposal company.</li> <li>Waste must be classified and labelled prior to recycling or disposal.</li> <li>Send to a licensed waste management company.</li> <li>Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.</li> </ul>

DURON TM/MC XL 15W-40

#### 000003000741

Version 3.0

Print Date 2016/11/08

#### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

IATA-DGR Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable for product as supplied.

#### **National Regulations**

TDG

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The components of this product are reported in the following inventories:			
DSL	On the inventory, or in compliance with the inventory		
TSCA	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.		
ELINCS	At least one component is not listed in EINECS but all such components are listed in ELINCS.		

#### **SECTION 16. OTHER INFORMATION**

For Copy of SDS	:	Internet: lubricants.petro-canada.ca/msds Western Canada, telephone: 1-800-661-1199; fax: 1-800-378- 4518 Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1- 800-201-6285 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285 For Product Safety Information: 1 905-804-4752
Prepared by	:	Product Safety: +1 905-804-4752
Revision Date	:	2016/11/08

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guid-

DURON TM/MC XL 15W-40

materials or in any process, unless specified in the text.

#### 000003000741

Version 3.0

material designated and may not be valid for such material used in combination with any other

Revision Date 2016/11/08 ance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific



Print Date 2016/11/08